


## Modular Jack - Pin in Paste






### Description

Connectors are often the only non SMT component and therefore require separate process to wave solder and manual assembly of the connectors. Inelco's Pin in Paste jacks are best suited for automatic assembly



### Advantages

- Reliability and yield
- Fully automated handling and soldering
- Easier to assemble than the long THT contacts
- More resistant to mechanical forces than SMT
- Custom contact length is available, for example 1.4 mm
- Perfect soldering without whisker effect and without rework
- High temperature withstanding housing of PA9T or PA10T for reflow soldering
- Tape and reel packaging
- Mylar or pick and place pad for top entry and angled type

Soldering Technology	THT	THR	PiP	SMT
	Through-Hole Technology	Through-Hole-Reflow	Pin in Paste	Surface Mount Technology
Contact Design				
Soldered Contacts				
Solder Process	Hand / Wave	Reflow	Reflow / Wave	Reflow / Wave
Plastic	PBT / FR52	PA9T / PA10T	PA9T / PA10T	PA9T / PA10T
Board Assembly	Manual	Manual	Pick and Place Machine	Pick and Place Machine

## Modular Jacks

INELCO has one of the broadest ranges of modular connectors, which INELCO named MODCON®. As a leading manufacturer of modular jacks we develop and improve our product according to our customer's needs.


### Features

- Low profile, short body
- Single or multi port
- with or without LEDs
- single or bi-color LEDs, many colors


### Specifications

- THT, THR, PiP, SMT, EDGE
- Cat5, Cat5e, Cat6, Cat6A
- unshielded or shielded
- with or without EMI tabs
- 6 ... 50 μ" gold plating, std 30 μ"

**Side Entry**  
Latch Down




**Side Entry**  
Latch Up




**Top Entry**  
Straight & Angled




**SMT, Card Edge**




**Harmonica**



**Doublestack**





**INELCO**<sup>®</sup>  
THE DISTINCTION

**modcon**<sup>®</sup>  
modular jacks

28 - 03 - 2017



INELCO the home of unparalleled quality and service in Interconnection and Electronic Components is a European driven company, manufacturing European ideas, solutions and quality in Asia. INELCO's mission is to fulfill the requirements of their partners and customers and remains the best choice for cost-effective solutions. INELCO is the supplier of interconnection and electronic components and systems for networking, telecommunications and industrial applications. INELCO's product range includes modular (Western) plugs and jacks (modcon<sup>®</sup>), with and without integrated transformers (intrajack<sup>®</sup>), shielded and unshielded as well as terminals (voice services<sup>®</sup>), SFPs (compu-shield<sup>®</sup>), M12 (circon<sup>®</sup>), discrete components (discom<sup>®</sup> transformers, coils and inductors), USBs and other additional products and services.



## modcon® - modular jacks


### Technical Specification

Voltage Rating	125 VAC
Current Rating	1.5 A
Contact Resistance	30 mΩ max.
Insulation Resistance	1,000 MΩ min.
Withstanding Voltage	1,000 V AC 60 Hz 1 min.
Housing	High Temp. Polycarbonate or Polyester, UL 94 V-0/ UL 94 V-2
Shield	Copper Alloy Nickel Plated T = 0.25 mm
Contacts	Phosphor Bronze
Plating	Gold over Nickel
Selective Goldplating	3/ 6/ 15/ 30/ 50 μ"
Durability	500 ... 2,500 Mating Cycles min.
Storage Temperature	-40°C to +85°C
Operation Temperature	-40°C to +85°C

Mates with Modular Plug Conforming to ANSI/TIA-1096-A

### Part Numbers

**J X C P (N N) Y Z - G**







#### Options:

- A: Angled
- CC: Contact Carrier
- C6: Cat6
- D: Dip
- DP: Dip Soldering Peg
- EDGE: Card Edge
- E5: Cat5e
- FE: Ferrum
- H: Horizontal
- LL: With LEDs
- LP: Low Profile
- LU: Latch Up
- O: High Profile
- PF: Front Peg
- Q: Economy Version
- SB: Short Body
- SMT: Surface Mounted Technology
- SW: Switch
- T6: Enhanced Shield with EMI-Tabs
- V: Vertical (Top Entry)
- W: White
- Z: Press Fit

**Top Entry 8P PCB Jack UTP**





JU88V



PC Board Layout  
Component Side Shown

**Top Entry 8P PCB Jack STP**




JS88VPF



PC Board Layout  
Component Side Shown

**Top Entry PCB Jack STP**





JS88VT6PF



PC Board Layout  
Component Side Shown

### Top Entry 8P PCB Jack UTP





JU88VD



PC Board Layout  
Component Side Shown

### Top Entry 8P SMT Jack STP




JS88VDSMT



PC Board Layout  
Component Side Shown

### Top Entry 4P, 6P, 8P SMT Jack UTP

JUCPVSMT






PC Board Layout  
Component Side Shown

Part Number	Type	DIM	"A±0.2"	"B±0.2"	"C"
JU44VSMT	4P		13.2	12.8	3.81
JU66VSMT	6P		13.2	12.8	6.35
JU88VSMT	8P		15.4	12.8	8.89

**Top Entry 8P SMT Jack UTP**





JU88VDSMT



PC Board Layout  
Component Side Shown

**Top Entry 4P, 6P, 8P PCB Jack UTP**

JUCPVD







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM		
		"A±0.2"	"B±0.2"	"C"
JU44VD	4P	11.2	7.62	3.81
JU66VD	6P	13.2	10.16	6.35
JU88VD	8P	15.2	11.43	8.89

**Top Entry 8P SMT Jack STP**



JS88VSMT



PC Board Layout  
Component Side Shown

### Top Entry 1\*N 8P PCB Jack UTP

JU880NV





PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"	"D"
JU8802V	1x2		27.4	28.0	13.70	23.80
JU8804V	1x4		54.8	55.4	41.10	51.20
JU8805V	1x5		68.5	69.1	54.80	64.90
JU8806V	1x6		82.2	82.8	68.50	78.60
JU8808V	1x8		109.6	102.2	95.90	106.00

### Top Entry 1\*N 8P PCB Jack STP

JS880NV







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JS8802V	1x2		28.6	23.8	13.70
JS8804V	1x4		56.0	51.2	41.10
JS8806V	1x6		83.4	78.6	68.50
JS8808V	1x8		110.8	106.0	95.90

**Top Entry L/P 8P PCB Jack STP 13.1 mm H**





JS88VLP



PC Board Layout  
Component Side Shown

**Top Entry L/P 8P SMT Jack UTP 12.7 mm H**





JU88VLPSMT



PC Board Layout  
Component Side Shown

**Top Entry L/P 8P PCB Jack DIP UTP 12.7 mm H**





JU88VLP



PC Board Layout  
Component Side Shown

### Top Entry 6P PCB Jack UTP




JUC6V



PC Board Layout  
Component Side Shown

### 45° 8P PCB Jack STP




JS88A



PC Board Layout  
Component Side Shown

### 45° 8P PCB Jack





JU88A



PC Board Layout  
Component Side Shown

Side Entry L/P 6P, 8P PCB Jack UTP

JUCPLP







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU66LP	6P		13.2	10.16	6.35
JU88LP	8P		15.1	11.43	8.89

Side Entry 6P, 8P SMT Jack Card Edge STP

JSCPEDGESMT







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"	"D"
JS66EDGESMT	6P		11.7	9.89	5.10	15.20
JS88EDGESMT	8P		14.4	11.94	7.14	17.24

Side Entry L/P 1\*4 8P PCB Jack UTP



JU8804LP



PC Board Layout  
Component Side Shown

### Side Entry 8P SMT Jack UTP


JU88ASMT



PC Board Layout  
Component Side Shown

### Side Entry 4P, 6P, 8P SMT Jack UTP

JUCPSMT3




PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"
JU44SMT3	4P		11.2	3.81
JU66SMT3	6P		13.2	6.35
JU88SMT3	8P		15.1	8.89

### Side Entry 8P Half PCB Jack UTP


JU88CC



PC Board Layout  
Component Side Shown


**Side Entry 1\*2 8P SMT Jack UTP**

JU8802LUSMT



**Side Entry 4P, 6P, 8P SMT Jack UTP**





JUCPSMT1



Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU44SMT1	4P		11.2	10.16	3.81
JU66SMT1	6P		13.2	12.16	6.35
JU88SMT1	8P		15.1	14.19	8.89

### Side Entry 6P, 8P SMT Jack UTP

JUCPSMT2







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"
JU66SMT2	6P		13.2	6.35
JU88SMT2	8P		15.1	8.89

### Side Entry 8P SMT Jack UTP





JU88DSMT



PC Board Layout  
Component Side Shown

### Side Entry 6P SMT Jack STP





JS66SMT3



PC Board Layout  
Component Side Shown

**Side Entry 8P SMT Jack STP**





JS88SMT2



PC Board Layout  
Component Side Shown

**Side Entry 1\*4 Mini L/P 6P PCB Jack STP**



JS6604LUT6



PC Board Layout  
Component Side Shown

### Side Entry 1\*N Mini L/P 8P PCB Jack UTP

JU880NLULP





PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU8801LULP	1X1		15.5	15.5	15.5
JU8802LULP	1X2		30.0	14.5	30.0
JU8803LULP	1X3		44.5	29.0	45.5
JU8804LULP	1X4		59.0	43.5	59.0
JU8805LULP	1X5		73.5	58.0	73.5
JU8806LULP	1X6		88.0	72.5	88.0
JU8808LULP	1X8		117.0	101.5	117.0

### Side Entry 1\*1, 1\*4 Mini L/P 8P PCB Jack Metal Feet UTP

JU880NLULPW






PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU8801LULPW	8P		16.1	16.60	16.60
JU8804LULPW	8P		58.0	58.45	58.45

**Side Entry 1\*N L/P 8P PCB Jack UTP**

JU800NLP







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	DIMENSIONS		
			"A±0.2"	"B±0.2"	"C"
JU8001LP	1X1		15.1		11.43
JU8002LP	1X2		30.4	13.97	25.40
JU8003LP	1X3		44.4	27.94	39.37
JU8004LP	1X4		58.4	41.91	53.34
JU8005LP	1X5		72.3	55.88	67.31
JU8006LP	1X6		86.3	69.85	81.28
JU8008LP	1X8		114.3	97.79	109.22

**Side Entry 1\*4, 1\*8 6P PCB Jack UTP**

JU660N






PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	DIMENSIONS			
			"A±0.2"	"B±0.2"	"C"	"D"
JU6604	1X4		47.78	34.14	44.31	
JU6608	1X8		93.29	79.66	89.82	44.91

### Side Entry Mini L/P 8P PCB Jack STP




JS88LULP



PC Board Layout  
Component Side Shown

### Side Entry L/P 10P PCB Jack STP





JS80LPPFT6



PC Board Layout  
Component Side Shown

### Side Entry L/P 10P PCB Jack STP





JS80LPT6



PC Board Layout  
Component Side Shown

**Side Entry 10P PCB Jack UTP**





JU80SB



PC Board Layout  
Component Side Shown

**Side Entry 10P PCB Jack STP**





JS80SB



PC Board Layout  
Component Side Shown

**Side Entry 10P PCB Jack STP**




JS80SBPF



PC Board Layout  
Component Side Shown

### Side Entry 1\*1, 1\*4 8P PCB Jack UTP

JU880NFE






PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU8801FE	1X1		14.1	11.43	
JU8804FE	1X4		58.4	41.91	53.34

### Side Entry 1\*4 6P PCB Jack UTP





JU6604FE



PC Board Layout  
Component Side Shown

**Side Entry L/P 8P PCB Jack STP**





JS88LPPF



PC Board Layout  
Component Side Shown

**Side Entry 4P, 6P, 8P PCB Jack UTP**

JUCPO





PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU44O	4P		11.2	7.62	3.81
JU66O	6P		13.2	10.16	6.35
JU88O	8P		15.3	11.43	8.89



Side Entry 1\*N 8P PCB Jack STP

JS880NPFT6






PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	DIMENSIONS		
			"A±0.2"	"B±0.2"	"C"
JS8801PFT6	1X1		16.00		11.43
JS8802PFT6	1X2		31.24	13.97	25.40
JS8803PFT6	1X3		45.21	27.94	39.37
JS8804PFT6	1X4		59.18	41.91	53.34
JS8805PFT6	1X5		73.15	55.88	67.32
JS8806PFT6	1X6		87.12	69.85	81.28
JS8808PFT6	1X8		115.06	97.79	109.22

### Side Entry 1\*N 8P PCB Jack UTP

JU800N







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU8001	1X1		15.20		11.43
JU8002	1X2		30.48	13.97	25.40
JU8003	1X3		44.45	27.94	39.37
JU8004	1X4		58.42	41.91	53.34
JU8005	1X5		73.15	55.88	67.32
JU8006	1X6		86.36	69.85	81.28
JU8008	1X8		114.30	97.79	109.22

**Side Entry 2\*N 8P PCB Doublestack UTP**

JU881N







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU8811	2X1		16.50		11.43
JU8812	2X2		30.48	13.97	25.40
JU8813	2X3		44.45	27.94	39.37
JU8814	2X4		58.42	41.91	53.34
JU8815	2X5		72.39	55.88	67.35
JU8816	2X6		86.36	69.85	81.28
JU8818	2X8		114.30	97.79	109.22

**Side Entry 2\*N 8P PCB Jack STP (Stamp)**

JS881NPFT6






PC Board Layout  
Component Side Shown

Part Number	DIM		"A±0.2"	"B±0.2"	"C"
	TYPE				
JS8812PFT6	2X2		31.24	13.97	25.40
JS8814PFT6	2X4		59.18	41.91	53.34
JS8815PFT6	2X5		73.15	55.88	67.35
JS8816PFT6	2X6		87.12	69.85	81.28
JS8818PFT6	2X8		115.06	97.79	109.22

**Side Entry 6P PCB Jack UTP**





JU66LU



PC Board Layout  
Component Side Shown

**Side Entry 8P PCB Jack Card Edge STP**




JS88LUEDGE



PC Board Layout  
Component Side Shown

**Side Entry 8P SMT PCB Jack STP**




JS88LUSMTT6



PC Board Layout  
Component Side Shown

### Side Entry L/P 8P LED Jack STP



JS88LLLUT6



PC Board Layout  
Component Side Shown

### Side Entry 8P LED Jack UTP




JU88LLLUSB



PC Board Layout  
Component Side Shown

### Side Entry L/P 8P LED Jack STP




JS88LLLULP



PC Board Layout  
Component Side Shown

**Top Entry 8P LED Jack UTP**





JU88LLV



PC Board Layout  
Component Side Shown

**Side Entry 8P LED Jack UTP**





JU88LL



PC Board Layout  
Component Side Shown

**Top Entry L/P 8P LED Jack UTP**





JU88LLVLP



PC Board Layout  
Component Side Shown

### Top Entry 8P LED Jack STP





JS88LLV



PC Board Layout  
Component Side Shown

### Top Entry L/P 8P LED Jack STP




JS88LLVLP



PC Board Layout  
Component Side Shown



**Side Entry 8P LED Jack STP**

JS88LLT6




**Side Entry 8P LED Jack STP**

JS88LLPF






**Side Entry 1\*2 8P LED Jack UTP**

JU8802LL



### Side Entry 1\*1, 1\*2, 1\*4 8P PCB Jack UTP

JU880NLU






PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"	"D"
JU8801LU	1X1		15.80		12.70	
JU8802LU	1X2		31.60	15.80	28.50	
JU8804LU	1X4		63.20	47.40	60.10	30.10

### Side Entry 1\*1, 1\*2, 1\*4 8P LED Jack UTP

JU880NLLLU






PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"	"D"
JU8801LLLU	1X1		15.80		12.70	
JU8802LLLU	1X2		31.60	15.80	28.50	
JU8804LLLU	1X4		47.40	31.60	44.30	



**Side Entry 1\*4 8P PCB Jack Card Edge STP**

JS8804EDGET6








**Top Entry 1\*4 8P LED Jack STP**

JS8804LLV



### Side Entry 1\*2, 1\*4 8P LED Jack STP

JS880NLLT6









PC Board Layout Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C±0.2"
JS8802LLT6	1X2		31.24	13.97	25.40
JS8804LLT6	1X4		59.18	41.91	53.34

### Side Entry 1\*4 8P LED Jack UTP


JU8804LL



PC Board Layout Component Side Shown

**Side Entry 1\*N 8P LED Jack STP**

JS880NLLLUT6





PC Board Layout  
Component Side Shown

LED Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"	"D"	"E"
JS8801LLLUT6	1X1		16.40		12.70	16.16	
JS8802LLLUT6	1X2		32.20	15.80	28.50	31.95	
JS8803LLLUT6	1X3		48.00	31.60	44.30	47.75	
JS8804LLLUT6	1X4		63.80	47.40	60.10	63.55	30.10
JS8808LLLUT6	1X8		127.00	110.60	123.30	127.00	61.65

### 45° 8P PCB Jack STP



JS88AQ



PC Board Layout  
Component Side Shown

### Side Entry 2\*1 8P LED Doublestack STP





JS8811LLT6PF



PC Board Layout  
Component Side Shown

**Side Entry 2\*N 8P LED Doublestack STP**




JS881NLLPFT6



Part Number	DIM		"A±0.2"	"B±0.2"	"C"	"D"
	TYPE					
JS8812LLPFT6	2X2		33.40	16.26	16.26	33.10
JS8813LLPFT6	2X3		49.45	32.52	32.52	49.15
JS8814LLPFT6	2X4		65.90	48.78	48.78	65.60
JS8816LLPFT6	2X6		98.43	81.30	81.30	98.13
JS8818LLPFT6	2X8		130.95	113.82	113.82	130.65

### C5e Side Entry 1\*N 8P PCB Jack STP

JS880NPF5T6







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JS8802PFE5T6	1x2		31.24	13.97	25.40
JS8804PFE5T6	1x4		59.18	41.91	53.34
JS8808PFE5T6	1x8		115.06	97.79	109.22

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

**C5e Side Entry 8P LED Jack STP**

JS88LLE5T6







PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

**C5e Side Entry 8P PCB Jack STP**

JS88E5T6





PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

### C5e Side Entry 1\*N 8P PCB Jack UTP

JU800NE5




PC Board Layout  
Component Side Shown

Part Number	TYPE DIM	"A±0.2"	"B±0.2"	"C"	Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
JU8001E5	1X1	15.20		11.43	1.0	65	30	0.1
JU8002E5	1X2	30.48	13.97	25.40	4.0	65	30	0.1
JU8003E5	1X3	44.45	27.94	39.37	8.0	64.9	30	0.1
JU8004E5	1X4	58.42	41.91	53.34	10.0	63	30	0.1
JU8005E5	1X5	73.15	55.88	67.32	16.0	58.9	30	0.2
JU8006E5	1X6	86.36	69.85	81.28	20.0	57	30	0.2
JU8008E5	1X8	114.30	97.79	109.22	25.0	55	30	0.2
					31.25	53.1	30	0.2
					62.5	47.1	24.1	0.3
					100.0	43	20	0.4






### C5e Side Entry 2\*N 8P PCB Doublestack STP


JS881NPF5T6



JU881NPF5



PC Board Layout  
Component Side Shown







Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JS8812...	2X2		31.24	13.97	25.40
JS8814....	2X4		59.18	41.91	53.34
JS8815...	2X5		73.15	55.88	67.35
JS8816...	2X6		87.12	69.85	81.28
JS8818...	2X8		115.06	97.79	109.22

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

**C5e Side Entry 1\*N 8P LED Jack STP**

JS880NLE5T6






PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

### C5e Side Entry 2\*N 8P LED Doublestack STP

JS881NLLPFE5T6






PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"	"D"
JS8811LLPFE5T6	2X1		17.10			16.88
JS8812LLPFE5T6	2X2		33.40	16.26	16.26	33.10
JS8813LLPFE5T6	2X3		49.45	32.52	32.52	49.15
JS8814LLPFE5T6	2X4		65.90	48.78	48.78	65.60
JS8816LLPFE5T6	2X6		98.43	81.30	81.30	98.13
JS8818LLPFE5T6	2X8		130.95	113.82	113.82	130.65

**C6 Side Entry PCB Jack UTP**

JU88C6LU






PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

**C6 Top Entry PCB Jack UTP**

JU88VC6







PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

**C6 Top Entry 8P+2P Switch PCB Jack UTP**

JU88VC6SW






PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

## modcon® - modular jacks

### C6 47.5° 8P PCB Jack UTP

JU88C6A






PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

### C6 Side Entry 8P PCB Jack STP

JS88C6LU






PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

### C6 Top Entry 8P PCB Jack STP

JS88VC6





PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

**C6 47.5° PCB Jack STP**




JS88C6A



Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

**C6 Top Entry 8P PCB Jack STP**




JS88VC6PF



Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

**C5e Top Entry 8P PCB Jack Press Fit STP**

JU88VE5Z




Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

## Modular Jack - Pin in Paste






### Description

Connectors are often the only non SMT component and therefore require separate process to wave solder and manual assembly of the connectors. Inelco's Pin in Paste jacks are best suited for automatic assembly



### Advantages

- Reliability and yield
- Fully automated handling and soldering
- Easier to assemble than the long THT contacts
- More resistant to mechanical forces than SMT
- Custom contact length is available, for example 1.4 mm
- Perfect soldering without whisker effect and without rework
- High temperature withstanding housing of PA9T or PA10T for reflow soldering
- Tape and reel packaging
- Mylar or pick and place pad for top entry and angled type

Soldering Technology	THT	THR	PiP	SMT
	Through-Hole Technology	Through-Hole-Reflow	Pin in Paste	Surface Mount Technology
Contact Design				
Soldered Contacts				
Solder Process	Hand / Wave	Reflow	Reflow / Wave	Reflow / Wave
Plastic	PBT / FR52	PA9T / PA10T	PA9T / PA10T	PA9T / PA10T
Board Assembly	Manual	Manual	Pick and Place Machine	Pick and Place Machine

## Modular Jacks

INELCO has one of the broadest ranges of modular connectors, which INELCO named MODCON®. As a leading manufacturer of modular jacks we develop and improve our product according to our customer's needs.

### Features

- Low profile, short body
- Single or multi port
- with or without LEDs
- single or bi-color LEDs, many colors

### Specifications

- THT, THR, PiP, SMT, EDGE
- Cat5, Cat5e, Cat6, Cat6A
- unshielded or shielded
- with or without EMI tabs
- 6 ... 50 μ" gold plating, std 30 μ"

**Side Entry**  
Latch Down




**Side Entry**  
Latch Up




**Top Entry**  
Straight & Angled




**SMT, Card Edge**



**Harmonica**



**Doublestack**



# MODCON® RJ45 INDUSTRIAL JACKS



# INELCO®

THE DISTINCTION



RJ45 connectors allow some motion between the mating parts, even when fully seated and locked, because it were originally developed for the typical environment of telephone applications. Today the RJ45 is standardized for many other applications like automotive, medical, networking, computer and industrial applications. Especially for the industrial application the RJ45s were never ever developed for. The harsh environment and the extended force to the mating point are the main problems. INELCO put a lot of effort into the development of a complete new style RJ45's. Even so the connectors look the same from the outside, all items were completely new designed and developed.



Industrial applications mean also higher temperatures and higher mechanic stress for the housings of the jacks. Therefore INELCO redesigned the housing by using a special polyamid based plastic, which withstands higher temperatures than standard high temp plastics, but is soft enough not to break under stress.



The extended working temperatures of -40°C to +85°C, but also shock and vibrations, are creating problems for standard magnetics. Special coils and wires have to be used.



The vibrations and the possible movement of the plug within the jack housing create discontinuity at standard modular jacks. INELCO developed a new contact shape which allows the contact better to follow the plug at movements without being levered.



For shock and vibrations the magnetics are secured encapsulated inside the frame. For continuity at wiggling the contacts get freely suspended.



Additional Features:



- additional space underneath the vertical version for additional space on the PCB, to be used for e.g. capacitors
- Diamond posts for better hold on the PCB
- same dimensions and footprint for all versions of the same style

Available Versions:

- without magnetics: CAT5e and CAT6
- with magnetics: Profinet, 10/100 BaseT and Gigabit Ethernet
- optional LED's
- various shield options
- optional tape and reel packing

Wiggle (Gorilla) Dynamic Test Setup

The wiggle test is a severe test that is used to evaluate the integrity of the mated plug/jack connection and the risk of loss of electrical continuity. Acceptance Criteria: No loss of electrical continuity of the mated connection and the shield. INELCO's RJ45s are developed and build to pass these tests without any loss of electrical continuity.




Accessories: PVC Dust Cover for RJ45 Jacks



INELCO's modcon<sup>®</sup> RJ45 industrial are a part of INELCO's premium plug series, which is a forward thinking development of enhanced modular plugs for use in industrial and high-speed data environments. Excellent electrical performance, Single-Step termination process (shield & contacts are crimped in 1 operation), 360 degree shield connection, slim design for use in high density applications and capability for field termination, are only some of the many advantages of this plug series.





**INELCO**<sup>®</sup>  
THE DISTINCTION

**modcon**<sup>®</sup>  
modular jacks

28 - 03 - 2017



INELCO the home of unparalleled quality and service in Interconnection and Electronic Components is a European driven company, manufacturing European ideas, solutions and quality in Asia. INELCO's mission is to fulfill the requirements of their partners and customers and remains the best choice for cost-effective solutions. INELCO is the supplier of interconnection and electronic components and systems for networking, telecommunications and industrial applications. INELCO's product range includes modular (Western) plugs and jacks (modcon<sup>®</sup>), with and without integrated transformers (intrajack<sup>®</sup>), shielded and unshielded as well as terminals (voice services<sup>®</sup>), SFPs (compu-shield<sup>®</sup>), M12 (circon<sup>®</sup>), discrete components (discom<sup>®</sup> transformers, coils and inductors), USBs and other additional products and services.



## modcon® - modular jacks


### Technical Specification

Voltage Rating	125 VAC
Current Rating	1.5 A
Contact Resistance	30 mΩ max.
Insulation Resistance	1,000 MΩ min.
Withstanding Voltage	1,000 V AC 60 Hz 1 min.
Housing	High Temp. Polycarbonate or Polyester, UL 94 V-0/ UL 94 V-2
Shield	Copper Alloy Nickel Plated T = 0.25 mm
Contacts	Phosphor Bronze
Plating	Gold over Nickel
Selective Goldplating	3/ 6/ 15/ 30/ 50 μ"
Durability	500 ... 2,500 Mating Cycles min.
Storage Temperature	-40°C to +85°C
Operation Temperature	-40°C to +85°C

Mates with Modular Plug Conforming to ANSI/TIA-1096-A

### Part Numbers

**J X C P (N N) Y Z - G**







#### Options:

- A: Angled
- CC: Contact Carrier
- C6: Cat6
- D: Dip
- DP: Dip Soldering Peg
- EDGE: Card Edge
- E5: Cat5e
- FE: Ferrum
- H: Horizontal
- LL: With LEDs
- LP: Low Profile
- LU: Latch Up
- O: High Profile
- PF: Front Peg
- Q: Economy Version
- SB: Short Body
- SMT: Surface Mounted Technology
- SW: Switch
- T6: Enhanced Shield with EMI-Tabs
- V: Vertical (Top Entry)
- W: White
- Z: Press Fit

**Top Entry 8P PCB Jack UTP**





JU88V



PC Board Layout  
Component Side Shown

**Top Entry 8P PCB Jack STP**




JS88VPF



PC Board Layout  
Component Side Shown

**Top Entry PCB Jack STP**





JS88VT6PF



PC Board Layout  
Component Side Shown

### Top Entry 8P PCB Jack UTP





JU88VD



PC Board Layout  
Component Side Shown

### Top Entry 8P SMT Jack STP




JS88VDSMT



PC Board Layout  
Component Side Shown

### Top Entry 4P, 6P, 8P SMT Jack UTP

JUCPVSMT






PC Board Layout  
Component Side Shown

Part Number	Type	DIM	"A±0.2"	"B±0.2"	"C"
JU44VSMT	4P		13.2	12.8	3.81
JU66VSMT	6P		13.2	12.8	6.35
JU88VSMT	8P		15.4	12.8	8.89

**Top Entry 8P SMT Jack UTP**





JU88VDSMT



PC Board Layout  
Component Side Shown

**Top Entry 4P, 6P, 8P PCB Jack UTP**

JUCPVD







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM		
		"A±0.2"	"B±0.2"	"C"
JU44VD	4P	11.2	7.62	3.81
JU66VD	6P	13.2	10.16	6.35
JU88VD	8P	15.2	11.43	8.89

**Top Entry 8P SMT Jack STP**



JS88VSMT



PC Board Layout  
Component Side Shown

### Top Entry 1\*N 8P PCB Jack UTP

JU880NV





PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"	"D"
JU8802V	1x2		27.4	28.0	13.70	23.80
JU8804V	1x4		54.8	55.4	41.10	51.20
JU8805V	1x5		68.5	69.1	54.80	64.90
JU8806V	1x6		82.2	82.8	68.50	78.60
JU8808V	1x8		109.6	102.2	95.90	106.00

### Top Entry 1\*N 8P PCB Jack STP

JS880NV







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JS8802V	1x2		28.6	23.8	13.70
JS8804V	1x4		56.0	51.2	41.10
JS8806V	1x6		83.4	78.6	68.50
JS8808V	1x8		110.8	106.0	95.90

**Top Entry L/P 8P PCB Jack STP 13.1 mm H**





JS88VLP



PC Board Layout  
Component Side Shown

**Top Entry L/P 8P SMT Jack UTP 12.7 mm H**





JU88VLPSMT



PC Board Layout  
Component Side Shown

**Top Entry L/P 8P PCB Jack DIP UTP 12.7 mm H**





JU88VLP



PC Board Layout  
Component Side Shown

### Top Entry 6P PCB Jack UTP




JUC6V



PC Board Layout  
Component Side Shown

### 45° 8P PCB Jack STP




JS88A



PC Board Layout  
Component Side Shown

### 45° 8P PCB Jack





JU88A



PC Board Layout  
Component Side Shown

**Side Entry L/P 6P, 8P PCB Jack UTP**

JUCPLP







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU66LP	6P		13.2	10.16	6.35
JU88LP	8P		15.1	11.43	8.89

**Side Entry 6P, 8P SMT Jack Card Edge STP**

JSCPEDGESMT







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"	"D"
JS66EDGESMT	6P		11.7	9.89	5.10	15.20
JS88EDGESMT	8P		14.4	11.94	7.14	17.24

**Side Entry L/P 1\*4 8P PCB Jack UTP**



JU8804LP



PC Board Layout  
Component Side Shown

### Side Entry 8P SMT Jack UTP


JU88ASMT



PC Board Layout  
Component Side Shown

### Side Entry 4P, 6P, 8P SMT Jack UTP

JUCPSMT3




PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"
JU44SMT3	4P		11.2	3.81
JU66SMT3	6P		13.2	6.35
JU88SMT3	8P		15.1	8.89

### Side Entry 8P Half PCB Jack UTP


JU88CC



PC Board Layout  
Component Side Shown


**Side Entry 1\*2 8P SMT Jack UTP**

JU8802LUSMT



**Side Entry 4P, 6P, 8P SMT Jack UTP**





JUCPSMT1



Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU44SMT1	4P		11.2	10.16	3.81
JU66SMT1	6P		13.2	12.16	6.35
JU88SMT1	8P		15.1	14.19	8.89

### Side Entry 6P, 8P SMT Jack UTP

JUCPSMT2






PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"
JU66SMT2	6P		13.2	6.35
JU88SMT2	8P		15.1	8.89

### Side Entry 8P SMT Jack UTP





JU88DSMT



PC Board Layout  
Component Side Shown

### Side Entry 6P SMT Jack STP





JS66SMT3



PC Board Layout  
Component Side Shown

**Side Entry 8P SMT Jack STP**





JS88SMT2



PC Board Layout  
Component Side Shown

**Side Entry 1\*4 Mini L/P 6P PCB Jack STP**



JS6604LUT6



PC Board Layout  
Component Side Shown

### Side Entry 1\*N Mini L/P 8P PCB Jack UTP

JU880NLULP





PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU8801LULP	1X1		15.5	15.5	15.5
JU8802LULP	1X2		30.0	14.5	30.0
JU8803LULP	1X3		44.5	29.0	45.5
JU8804LULP	1X4		59.0	43.5	59.0
JU8805LULP	1X5		73.5	58.0	73.5
JU8806LULP	1X6		88.0	72.5	88.0
JU8808LULP	1X8		117.0	101.5	117.0

### Side Entry 1\*1, 1\*4 Mini L/P 8P PCB Jack Metal Feet UTP

JU880NLULPW






PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU8801LULPW	8P		16.1	16.60	16.60
JU8804LULPW	8P		58.0	58.45	58.45

**Side Entry 1\*N L/P 8P PCB Jack UTP**

JU800NLP






PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	DIMENSIONS		
			"A±0.2"	"B±0.2"	"C"
JU8001LP	1X1		15.1	11.43	
JU8002LP	1X2		30.4	22.86	25.40
JU8003LP	1X3		44.4	34.29	39.37
JU8004LP	1X4		58.4	45.72	53.34
JU8005LP	1X5		72.3	57.15	67.31
JU8006LP	1X6		86.3	68.58	81.28
JU8008LP	1X8		114.3	97.79	109.22

**Side Entry 1\*4, 1\*8 6P PCB Jack UTP**

JU660N






PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	DIMENSIONS			
			"A±0.2"	"B±0.2"	"C"	"D"
JU6604	1X4		47.78	34.14	44.31	
JU6608	1X8		93.29	79.66	89.82	44.91

### Side Entry Mini L/P 8P PCB Jack STP





JS88LULP



PC Board Layout  
Component Side Shown

### Side Entry L/P 10P PCB Jack STP





JS80LPPFT6



PC Board Layout  
Component Side Shown

### Side Entry L/P 10P PCB Jack STP





JS80LPT6



PC Board Layout  
Component Side Shown

**Side Entry 10P PCB Jack UTP**





JU80SB



PC Board Layout  
Component Side Shown

**Side Entry 10P PCB Jack STP**





JS80SB



PC Board Layout  
Component Side Shown

**Side Entry 10P PCB Jack STP**




JS80SBPF



PC Board Layout  
Component Side Shown

### Side Entry 1\*1, 1\*4 8P PCB Jack UTP

JU880NFE






PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU8801FE	1X1		14.1		11.43
JU8804FE	1X4		58.4	41.91	53.34

### Side Entry 1\*4 6P PCB Jack UTP





JU6604FE



PC Board Layout  
Component Side Shown

**Side Entry L/P 8P PCB Jack STP**





JS88LPPF



PC Board Layout  
Component Side Shown

**Side Entry 4P, 6P, 8P PCB Jack UTP**

JUCPO





PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU44O	4P		11.2	7.62	3.81
JU66O	6P		13.2	10.16	6.35
JU88O	8P		15.3	11.43	8.89



**Side Entry 1\*N 8P PCB Jack STP**

JS880NPFT6






PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	DIMENSIONS		
			"A±0.2"	"B±0.2"	"C"
JS8801PFT6	1X1		16.00		11.43
JS8802PFT6	1X2		31.24	13.97	25.40
JS8803PFT6	1X3		45.21	27.94	39.37
JS8804PFT6	1X4		59.18	41.91	53.34
JS8805PFT6	1X5		73.15	55.88	67.32
JS8806PFT6	1X6		87.12	69.85	81.28
JS8808PFT6	1X8		115.06	97.79	109.22

### Side Entry 1\*N 8P PCB Jack UTP

JU800N







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU8001	1X1		15.20		11.43
JU8002	1X2		30.48	13.97	25.40
JU8003	1X3		44.45	27.94	39.37
JU8004	1X4		58.42	41.91	53.34
JU8005	1X5		73.15	55.88	67.32
JU8006	1X6		86.36	69.85	81.28
JU8008	1X8		114.30	97.79	109.22

**Side Entry 2\*N 8P PCB Doublestack UTP**

JU881N







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JU8811	2X1		16.50		11.43
JU8812	2X2		30.48	13.97	25.40
JU8813	2X3		44.45	27.94	39.37
JU8814	2X4		58.42	41.91	53.34
JU8815	2X5		72.39	55.88	67.35
JU8816	2X6		86.36	69.85	81.28
JU8818	2X8		114.30	97.79	109.22

**Side Entry 2\*N 8P PCB Jack STP (Stamp)**

JS881NPFT6






PC Board Layout  
Component Side Shown

Part Number	DIM		"A±0.2"	"B±0.2"	"C"
	TYPE				
JS8812PFT6	2X2		31.24	13.97	25.40
JS8814PFT6	2X4		59.18	41.91	53.34
JS8815PFT6	2X5		73.15	55.88	67.35
JS8816PFT6	2X6		87.12	69.85	81.28
JS8818PFT6	2X8		115.06	97.79	109.22

**Side Entry 6P PCB Jack UTP**





JU66LU



PC Board Layout  
Component Side Shown

**Side Entry 8P PCB Jack Card Edge STP**




JS88LUEDGE



PC Board Layout  
Component Side Shown

**Side Entry 8P SMT PCB Jack STP**




JS88LUSMTT6



PC Board Layout  
Component Side Shown

### Side Entry L/P 8P LED Jack STP



JS88LLLUT6



PC Board Layout  
Component Side Shown

### Side Entry 8P LED Jack UTP




JU88LLLUSB



PC Board Layout  
Component Side Shown

### Side Entry L/P 8P LED Jack STP




JS88LLLULP



PC Board Layout  
Component Side Shown

**Top Entry 8P LED Jack UTP**





JU88LLV



PC Board Layout  
Component Side Shown

**Side Entry 8P LED Jack UTP**





JU88LL



PC Board Layout  
Component Side Shown

**Top Entry L/P 8P LED Jack UTP**





JU88LLVLP



PC Board Layout  
Component Side Shown

### Top Entry 8P LED Jack STP





JS88LLV



PC Board Layout  
Component Side Shown

### Top Entry L/P 8P LED Jack STP



JS88LLVLP



PC Board Layout  
Component Side Shown


**Side Entry 8P LED Jack STP**

JS88LLT6



TYPE<1>

TYPE<2>



TYPE<1>




TYPE<2>

PC Board Layout  
Component Side Shown

PC Board Layout  
Component Side Shown

**Side Entry 8P LED Jack STP**



JS88LLPF



PC Board Layout  
Component Side Shown

**Side Entry 1\*2 8P LED Jack UTP**




JU8802LL



PC Board Layout  
Component Side Shown

### Side Entry 1\*1, 1\*2, 1\*4 8P PCB Jack UTP

JU880NLU







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"	"D"
JU8801LU	1X1		15.80		12.70	
JU8802LU	1X2		31.60	15.80	28.50	
JU8804LU	1X4		63.20	47.40	60.10	30.10

### Side Entry 1\*1, 1\*2, 1\*4 8P LED Jack UTP

JU880NLLLU






PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"	"D"
JU8801LLLU	1X1		15.80		12.70	
JU8802LLLU	1X2		31.60	15.80	28.50	
JU8804LLLU	1X4		47.40	31.60	44.30	


**Side Entry 1\*4 8P PCB Jack Card Edge STP**

JS8804EDGET6








**Top Entry 1\*4 8P LED Jack STP**

JS8804LLV



### Side Entry 1\*2, 1\*4 8P LED Jack STP

JS880NLLT6









PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C±0.2"
JS8802LLT6	1X2		31.24	13.97	25.40
JS8804LLT6	1X4		59.18	41.91	53.34

### Side Entry 1\*4 8P LED Jack UTP


JU8804LL



PC Board Layout  
Component Side Shown

**Side Entry 1\*N 8P LED Jack STP**

JS880NLLLUT6





PC Board Layout  
Component Side Shown

LED Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"	"D"	"E"
JS8801LLLUT6	1X1		16.40		12.70	16.16	
JS8802LLLUT6	1X2		32.20	15.80	28.50	31.95	
JS8803LLLUT6	1X3		48.00	31.60	44.30	47.75	
JS8804LLLUT6	1X4		63.80	47.40	60.10	63.55	30.10
JS8808LLLUT6	1X8		127.00	110.60	123.30	127.00	61.65

### 45° 8P PCB Jack STP



JS88AQ



PC Board Layout  
Component Side Shown

### Side Entry 2\*1 8P LED Doublestack STP





JS8811LLT6PF



PC Board Layout  
Component Side Shown

**Side Entry 2\*N 8P LED Doublestack STP**




JS881NLLPFT6



Part Number	DIM		"A±0.2"	"B±0.2"	"C"	"D"
	TYPE					
JS8812LLPFT6	2X2		33.40	16.26	16.26	33.10
JS8813LLPFT6	2X3		49.45	32.52	32.52	49.15
JS8814LLPFT6	2X4		65.90	48.78	48.78	65.60
JS8816LLPFT6	2X6		98.43	81.30	81.30	98.13
JS8818LLPFT6	2X8		130.95	113.82	113.82	130.65

### C5e Side Entry 1\*N 8P PCB Jack STP

JS880NPF5T6







PC Board Layout  
Component Side Shown

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JS8802PFE5T6	1x2		31.24	13.97	25.40
JS8804PFE5T6	1x4		59.18	41.91	53.34
JS8808PFE5T6	1x8		115.06	97.79	109.22

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

**C5e Side Entry 8P LED Jack STP**

JS88LLE5T6







PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

**C5e Side Entry 8P PCB Jack STP**

JS88E5T6





PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

### C5e Side Entry 1\*N 8P PCB Jack UTP

JU800NE5







PC Board Layout  
Component Side Shown

Part Number	TYPE DIM	"A±0.2"	"B±0.2"	"C"	Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
JU8001E5	1X1	15.20		11.43	1.0	65	30	0.1
JU8002E5	1X2	30.48	13.97	25.40	4.0	65	30	0.1
JU8003E5	1X3	44.45	27.94	39.37	8.0	64.9	30	0.1
JU8004E5	1X4	58.42	41.91	53.34	10.0	63	30	0.1
JU8005E5	1X5	73.15	55.88	67.32	16.0	58.9	30	0.2
JU8006E5	1X6	86.36	69.85	81.28	20.0	57	30	0.2
JU8008E5	1X8	114.30	97.79	109.22	25.0	55	30	0.2
					31.25	53.1	30	0.2
					62.5	47.1	24.1	0.3
					100.0	43	20	0.4

**C5e Side Entry 2\*1 8P PCB Doublestack STP**

JS8811PFE5T6




PC Board Layout  
Component Side Shown




Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

### C5e Side Entry 2\*N 8P PCB Doublestack STP


JS881NPF5T6



JU881NPF5



PC Board Layout  
Component Side Shown





Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"
JS8812...	2X2		31.24	13.97	25.40
JS8814....	2X4		59.18	41.91	53.34
JS8815...	2X5		73.15	55.88	67.35
JS8816...	2X6		87.12	69.85	81.28
JS8818...	2X8		115.06	97.79	109.22

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

**C5e Side Entry 1\*N 8P LED Jack STP**

JS880NLE5T6






PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

### C5e Side Entry 2\*N 8P LED Doublestack STP

JS881NLLPFE5T6






PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4

Part Number	TYPE	DIM	"A±0.2"	"B±0.2"	"C"	"D"
JS8811LLPFE5T6	2X1		17.10			16.88
JS8812LLPFE5T6	2X2		33.40	16.26	16.26	33.10
JS8813LLPFE5T6	2X3		49.45	32.52	32.52	49.15
JS8814LLPFE5T6	2X4		65.90	48.78	48.78	65.60
JS8816LLPFE5T6	2X6		98.43	81.30	81.30	98.13
JS8818LLPFE5T6	2X8		130.95	113.82	113.82	130.65

**C6 Side Entry PCB Jack UTP**

JU88C6LU






PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

**C6 Top Entry PCB Jack UTP**

JU88VC6







PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

**C6 Top Entry 8P+2P Switch PCB Jack UTP**

JU88VC6SW






PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

## modcon® - modular jacks

### C6 47.5° 8P PCB Jack UTP

JU88C6A







PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

### C6 Side Entry 8P PCB Jack STP

JS88C6LU






PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

### C6 Top Entry 8P PCB Jack STP

JS88VC6





PC Board Layout  
Component Side Shown

Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

**C6 47.5° PCB Jack STP**




JS88C6A



Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

**C6 Top Entry 8P PCB Jack STP**




JS88VC6PF



Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	75.0	35.5	0.1
4.0	75.0	35.5	0.1
10.0	74.0	35.5	0.1
16.0	69.9	35.5	0.1
25.0	66.0	35.5	0.1
31.25	64.1	34.1	0.1
62.5	58.1	28.1	0.1
100.0	54.0	24.0	0.2
200.0	48.0	18.0	0.3
250.0	46.0	16.0	0.3

**C5e Top Entry 8P PCB Jack Press Fit STP**

JU88VE5Z



Frequency MHz	Near-End Cross Talk dB, Min.	Return Loss dB, Min.	Attenuation dB, Max.
1.0	65	30	0.1
4.0	65	30	0.1
8.0	64.9	30	0.1
10.0	63	30	0.1
16.0	58.9	30	0.2
20.0	57	30	0.2
25.0	55	30	0.2
31.25	53.1	30	0.2
62.5	47.1	24.1	0.3
100.0	43	20	0.4